



- Note:
1. Rating : DC 12V 50mA
 2. Contact Resistance : $\leq 50m\Omega$
 3. Insulation Resistance: DC500V 1Minute
 4. Operating Temperature Range: $-25^{\circ}C+80^{\circ}C$
 5. Ambient Humidity Used: $\leq 85\%RH$
 6. Operating Force : $150\pm 80gf$
 7. Operating Life : 50,000Cycles

PCB Layout(Pattern side)

ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Contact Spring	—	1	Beryloy	Ag Plated	—
④	Terminal	—	5	Phosphor Bronze	Ag Plated	—
③	Base	—	1	LCP	Black	—
②	Cover	—	1	SUS	Natural	—
①	KNOB	—	1	PA46	RED	—

APPROVALS	DATE	TITLE
DRAWN JKUN.LU	2013/10/8	TOGGLE SWITCHES
OKHRO ELECTRONICS CO.,LTD		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	PROJ:	SHEET
	A		NEW				30~12.5 ±0.30	±2°	mm	1:1	K3-1288S	1 OF 1
							10~30 ±0.20					
							5~10 ±0.15					
							~5 ±0.10					