



PCB Layout(Pattern side) Circuit Diagram

PART NO	H	L	F
A	4.3	2.80	φ3.40
C	5	3.50	φ3.40
D	5.5	4.00	φ3.40
E	6	4.50	φ3.40
G	7	5.50	φ3.20
I	8	6.50	φ3.20
K	9	7.50	φ3.20
L	9.5	8.00	φ3.20

NO.2	
PART NO	vigor
1	90±30
2	130±30
3	180±30
4	250±30
5	350±50

NO.3	
PART NO	MATERIAL/QTY
S	SUS/1PC
C	C5210/1PC
D	SUS/2PCS
F	C5210/2PCS

NO.4-NO.5	
PART NO	NOTE
01~99	SERIAL NUMBER

⑥	Trestle	—	1	SPCC	Plating Nickel	—
⑤	Terminal	—	2	Brass(0.30)	Plating silver	—
④	Contact	—	1	F.Ag/SUS	Plating silver	—
③	Base	—	1	Nylon	Black	—
②	Cover	—	1	SPCC	Plating Nickel	—
①	Keystoke	—	1	Nylon	Black	—

APPROVALS		DATE	
DRAWN	J.X.Zhang	DATE	2013/5/30

CHECKED		TITLE:	TACT SWITCHS
APPROVALS		PART NO.	K2-1102BG-□□□W-□□
TOLERANCES ARE	30~12.5 ±0.30 10~30 ±0.20 5~10 ±0.15 ~5 ±0.10	ANGLE	±2°
		UNIT:	mm
		SCALE:	1:1
		DRAWING NO.	
		SHEET	1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	B		NEW			
	A					