


- NOTES:
1. CONTACT CURRENT RATING: 12V 1A.
  2. CONTACT RESISTANCE: 50mΩ MAX.;
  3. INSULATION RESISTANCE: 100M MIN. 500V DC;
  4. DIELECTRIC WITHSTANDING: 500V AC MIN.;
  5. DURABILITY: 5,000 CYCLES MIN.;
  6. CONNECTOR MATING FORCES: 29.4N (3.00kgf) MAX.;
  7. CONNECTOR UNMATING FORCES: 2.94N(0.30kgf) MIN.;



ITEM	PART NAME	Serial number	QTY.	MATERIAL	FINISHING	REMARK
⑨	Bond					
⑧	Terminal		2	Copper Alloy	Plating Ni	
⑦	Cover		1	Nylon	Block	UL 94V-0
⑥	Housing		1	Nylon	Block	UL 94V-0
⑤	Terminal 5		1	Copper Alloy	Plating Au	
④	Terminal 4		1	Copper Alloy	Plating Au	
③	Terminal 3		1	Copper Alloy	Plating Au	
②	Terminal 2		1	Copper Alloy	Plating Au	
①	Terminal 1		1	Copper Alloy	Plating Au	

APPROVALS	DATE
DRAWN	QIFENG.XU 2014.11.28

CHECKED		TITLE:	
APPROVALS		PHONE JACK (防水)	
TOLERANCES ARE		PART NO. PU-614	
30 <sup>±</sup> 以上	±0.30	ANGLE	SCALE: 1:1
10~30	±0.20	UNIT: mm	PROJ.
5~10	±0.15	±Z	SHEET 1 OF 1
~5	±0.10	DRAWING NO.	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

**OKHRO**  
ELECTRONICS CO.,LTD