


Rating: 0.5A 30V DC
 Contact Resistance: 100 mΩ Max.
 Operating temperature: -20℃~70℃
 Operating force: 3-20N
 Operating Life: 5,000cycles



CIRCUIT DIAGRAM

| | | | |
|---------------------|-----------|-----------------|------------|
| ② Terminal | 6 | Phosphor bronze | Au Plating |
| ① Housing | 1 | Nylon | Black |
| ITEM | PART NAME | TERN NO. | QTY. |
| APPROVALS | | DATE | |
| DRAWN | J.X.Zhang | 2013/11/11 | |
| ELECTRONICS CO.,LTD | | | |
| PHONE JACKS | | | |
| TITLE: | | PART NO. | PJ-3310 |
| CHECKED | | SCALE: | 1:1 |
| APPROVALS | | UNIT: | mm |
| TOLERANCES ARE | | ANGLE | ±2' |
| 30 ^{±0.15} | ±0.30 | | |
| 10 ^{±0.20} | ±0.20 | | |
| 5 ^{±0.10} | ±0.15 | | |
| ~5 | ±0.10 | | |
| DRAWING NO. | | SHEET 1 OF 1 | |

| | | | | | | |
|---------|------|-------|--------------|---------|--------|--------|
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
| | A | | NEW | | | |